



## Mini Mobile Barcode Scanner for Android OTG devices

### Features

- 1D Mini Mobile barcode scanners are designed for Android OTG devices especially.
- DC9257A: Plug & Play, No need extra driver
- DC9267A: Wearing form design frees operator's hands to move packages, products or materials, helping to improve efficiency and productivity.
- Lightweight, ergonomically designed for easy operation
- With application, DC92xx series make Android OTG devices become data collector economically.



### Specifications :

Model Name	DC9257A	DC9267A
Engine	CCD ENGINE	

### Performance Characteristics

• Light source	610nm~640nm Red LED	
• Depth of field	UPCA (13mil) : 50mm~620mm EAN13 (13mil) : 50mm~610mm	
• Scan speed	300 scans/sec	
• Best resolution	3 mil	
• Scan Angle	Pitch $\pm 60^\circ$ @ $0^\circ$ Roll and $0^\circ$ Skew Roll $\pm 30^\circ$ @ Pitch and $0^\circ$ Skew Skew $\pm 60^\circ$ @ Roll and $0^\circ$ Pitch	
• Interface	Micro USB/ Mini USB (DC9267A with extension cable)	
• Print contrast	$\geq 30\%$	
• Symbolologies	EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar, Code 128, Code 93, ITF-6, ITF-14, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, GS1 Databar, Code 39, Code 11, MSI-Plessey, Plessey.	

### Electrical Characteristics

• Input voltage	Smart Phone / Tablet Power
• Current - operating	85 mA max

### Physical Characteristics

• Dimension (L * W * H)	43 X 40 X 16 mm	43 X 34 X 16 mm (without cable) 59 X 20 X 12 mm (Holder, without strap)
• Color of housing	Black	
• Weight	20 g	48 g

### Environment

• Temperature-operation	$0^\circ\text{C}$ to $50^\circ\text{C}$
• Temperature-storage	$-10^\circ\text{C}$ to $60^\circ\text{C}$
• Humidity-operation	5% to 95% relative humidity, non-condensing

Product specification is subject to change without notice.

RIOTEC CO., LTD.

8F., 196-2, DaTong Rd., Sec. 3, Xizhi Dist., New Taipei City 221, Taiwan

TEL : +886-2-8647-1828

FAX : +886-2-8647-1800

E-mail : sales@riotec.com.tw

Web : www.riotec.com.tw