

Product Name: Fanless Industry PC		
Product No.:	K900-N2800	K900-D2550
Order Information	12V Input: (N2800/1GB RAM/16GB SSD/12V) 8~28V Input: US\$291(N2800/1GB RAM/16GB SSD/ Wide Voltage)	12V Input: (D2550/1GB RAM/16GB SSD/12V) 8~28V Input: (D2550/1GB RAM/16GB SSD/ Wide Voltage)
Optional Peripheral:	Wifi 802.11n: Bluetooth: 2GB RAM: 4GB RAM: 500GB HDD:	Wifi 802.11n: Bluetooth: 2GB RAM: 4GB RAM: 500GB HDD:
in Board	•Intel® Atom™ N2800 Dual Core processor, 1.86GHz, 1M Cache •Integrated Intel GMA 3650	•Intel® Atom™ D2550 Dual Core processor, 1.86GHz •Integrated Intel GMA 3650
Main Memory	•1 x DDR3 , support up to 4 GB DDR3 1333/800	•1 x DDR3 SO-DIMM socket, support up to 4 GB DDR3 1333/800 SDRAM
Storage	•1 x 2.5" SATA HDD drive bay	•2 x 2.5" SATA HDD drive bay
Lan	•Realtek RT8111E, 10/100/1000M, Support PXE, Wake on Lan	•Realtek RT8111E, 10/100/1000M, Support PXE, Wake on Lan
Audio	•Realtek ALC662	•Realtek ALC662
Watchdog Timer	•255 levels, 0~255 sec	•255 levels, 0~255 sec
BIOS	•AMI 16MB DPI Flash ROM	•AMI 16MB DPI Flash ROM
Expansion	•2 x Mini-PCle socket onboard •Default: support optional Wi-Fi module •Option: support 3G module	•2 x Mini-PCle socket onboard •Default: support optional Wi-Fi module •Option: support 3G module
I/O Interface-Front	•Power on/ off switch	• Power on/ off switch
I/O Interface-Rear	•4 x USB 2.0 •2 x RJ45 •1 x VGA •1 x HDMI •1 x Audio •4x COM •1x DC IN •2 x Antenna holes (Either optional Wi-Fi or Mobile wireless module)	•6 x USB 2.0+2x RS232 •1 x RJ45 •1 x VGA •1 x HDMI •1 x MIC-in •1 x Audio •1x DC IN •2 x Antenna holes (Either optional Wi-Fi or Mobile wireless module)
Power Requirements	•12V DC IN / 8~28V Wide Voltage input(Optional)	•12V DC IN / 8~28V Wide Voltage input(Optional)
Dimensions	•210 mm (W) x 188 mm (D) x 50mm (H)	•210 mm (W) x 188 mm (D) x 50mm (H)
Construction	•Aluminum Chassis	•Aluminum Chassis
Environment	•Operating temperature: Ambient with air flow: -10°C to 60°C (with industrial grade devices)(According to IEC60068-2-1, IEC60068-2-2, IEC60068-2-14) •Storage temperature: -10°C ~ 60°C •Relative humidity: 10% to 93% (Non-condensing) •Anti-Vibration: 5Hz~500Hz/1Grms/3Axis •Anti-Shock: 15G, 11ms Duration	•Operating temperature: Ambient with air flow: -10°C to 60°C (with industrial grade devices)(According to IEC60068-2-1, IEC60068-2-2, IEC60068-2-14) •Storage temperature: -20°C ~ 80°C •Relative humidity: 10% to 93% (Non-condensing) •Anti-Vibration: 5Hz~500Hz/1Grms/3Axis •Anti-Shock: 15G, 11ms Duration

Contact to:

mobilator.plTM

