

<b>Product Name: Fanless Industry PC</b>	
<b>Product No.:</b>	K802-N2800
<b>Order Information</b>	<b>12V Input: (N2800/1GB RAM/16GB SSD/12V)</b> <b>8~28V Input: (N2800/1GB RAM/16GB SSD/ Wide Voltage)</b>
<b>Optional Peripheral:</b>	Wifi 802.11n: 2GB RAM: 500GB HDD:
<b>Main Board</b>	•Intel® Atom™ N2800 Dual Core processor, 1.86GHz, 1M Cache •Integrated Intel GMA 3650
<b>Main Memory</b>	•1 x DDR3 , support up to 2 GB DDR3 1333/800
<b>Storage</b>	•1 x 2.5" SATA HDD drive bay
<b>Lan</b>	•Realtek RT8111E, 10/100/1000M, Support PXE, Wake on Lan
<b>Audio</b>	•Realtek ALC662
<b>Watchdog Timer</b>	•255 levels, 0~255 sec
<b>BIOS</b>	•AMI 16MB DPI Flash ROM
<b>Expansion</b>	•2 x Mini-PCIe socket onboard •Default: support optional Wi-Fi module •Option: support 3G module
<b>I/O Interface-Front</b>	•Power on/ off switch
<b>I/O Interface-Rear</b>	•4 x USB 2.0 •2 x RJ45 •1 x VGA •1 x HDMI •1 x Audio •2x COM •1x 12V DC IN •1x Antenna holes (Either optional Wi-Fi or Mobile wireless module)
<b>Power Requirements</b>	•12V DC IN
<b>Dimensions</b>	•176 mm (W) x 110 mm (D) x 59mm (H)
<b>Construction</b>	•Aluminum Chassis
<b>Environment</b>	•Operating temperature: Ambient with air flow: -10°C to 60°C (with industrial grade devices)(According to IEC60068-2-1, IEC60068-2-2, IEC60068-2-14) •Storage temperature: -20°C ~ 80°C •Relative humidity: 10% to 93% (Non-condensing) •Anti-Vibration: 5Hz~500Hz/1Grms/3Axis •Anti-Shock: 15G, 11ms Duration

Contact to:

**mobilator.pl**<sup>TM</sup>

